


Introduction

EZVIZ products have been designed for your entertainment, communication and security. When you install the EZVIZ APP on your smartphone or tablet, EZVIZ devices will be connected to the cloud via their QR code and will immediately be online. With EZVIZ, you can watch your child's progress when you are away, keep an eye on your home, interact with your four-legged friends and prevent household accidents.

Main Features



Dimensions



Specifications

Model	Specifications		
Image sensor 1/2.7" Progressive Scan CMOS Shutter Speed Self-adaptive shutter #mm@ F1.6, viewing angle: 48" (Vertical), 91" (Horizontal), 108" (Diagonal) #mm@ F1.6, viewing angle: 30" (Vertical), 56" (Horizontal), 108" (Diagonal) #mm@ F1.6, viewing angle: 30" (Vertical), 56" (Horizontal), 66" (Diagonal) #mm@ F1.6, viewing angle: 30" (Vertical), 56" (Horizontal), 66" (Diagonal) #mm@ F1.6, viewing angle: 30" (Vertical), 56" (Horizontal), 66" (Diagonal) #mm@ F1.6, viewing angle: 30" (Vertical), 56" (Horizontal), 66" (Diagonal) #mm@ F1.6, viewing angle: 30" (Vertical), 56" (Horizontal), 66" (Diagonal) #mm@ F1.6, viewing angle: 30" (Vertical), 56" (Horizontal), 108" (Diagonal) #mm@ F1.6, viewing angle: 30" (Vertical), 56" (Horizontal), 108" (Diagonal) #mm@ F1.6, viewing angle: 30" (Vertical), 56" (Horizontal), 108" (Diagonal) #mm@ F1.6, viewing angle: 30" (Vertical), 56" (Horizontal), 108" (Diagonal) #mm@ F1.6, viewing angle: 30" (Vertical), 56" (Horizontal), 108" (Diagonal) #mm@ F1.6, viewing angle: 30" (Vertical), 56" (Horizontal), 108" (Diagonal) #mm@ F1.6, viewing angle: 30" (Vertical), 56" (Horizontal), 108" (Horizontal),	Model	CS-H8c Pro (3K)	
Shutter Speed Self-adaptive shutter Lens dmm@ F1.6, wewing angle: 48" (Vertica), 91" (Horizontal), 108" (Diagonal) PT Angle Pan: 350" , Tilt: 80" Minimum Illumination 0.5 Lux @(F1.6, AGC ON), 0 Lux with IR (* data is obtained from EZVIZ laboratories) Lens Mount M12 DNR 3D DNR WDR Digital WDR Black & White Night Vision 30m/98t Video & Audio Max: 30fps; Self-Adaptive during network transmission Video Compression H. 265 / H. 266 H. 265 Type Main Profile Video Bit Rate Ultra-HD; Hi-Def; Standard. Adaptive bit rate. Audio Bit Rate Self-Adaptive Network Very Call Self Call Se			
Amm@ F1.6, viewing angle: 48" (Vertica), 91" (Horizontal), 108" (Diagonal) 6mm@ F1.6, viewing angle: 30" (Vertica), 56" (Horizontal), 66" (Diagonal) 7mm gP1.6, viewing angle: 30" (Vertica), 56" (Horizontal), 66" (Diagonal) 7mm gP1.6, 49 mai 350" 7 tht 80" 7mt s80" 7mt s8		-	
Fame	Shutter Speed	Self-adaptive shutter	
Frage Fin. Sevinip angle: 30" (Vertica), 56" (Horizontal), 66" (Diagonal) Minimum Illumination O.5 Lux @(FL6, AGC ON), 0 Lux with IR (* data is obtained from EZVIZ laboratories) Lens Mount M12 Day & Night IR-cut filter with auto switch DNR 3D DNR WDR Digital WDR Black & White Night Vision 3D myS8ft Video & Audio Max. Resolution 2880*1620 Frame Rate Max: 30hps; Self-Adaptive during network transmission Video Compression H.265 / H.264 H.265 Type Main Profile Video Sit Rate Olitra-Hib; Hi-Def; Standard. Adaptive bit rate. Audio Bit Rate Self-Adaptive Network Wi-Fi Standard IEEE802.11b, 802.11g, 802.11n Frequency Range 2.4 GHz ~ 2.4835 GHz Wi-Fi Standard IEEE802.11b, 802.11g, 802.11n Frequency Range 2.4 GHz ~ 2.4835 GHz Wi-Fi Pairing AP pairing Protocol EZVIZ Cloud proprietary protocol Wi-Fi Pairing AP pairing Protocol EZVIZ cloud proprietary protocol <	Lens	4mm@ F1.6, viewing angle: 48° (Vertica), 91° (Horizontal), 108° (Diagonal)	
Minimum Illumination M12			
Lens Mount M12 Day & Night IR-cut filter with auto switch DNR 30 DNR WDR Digital WDR Black & White Night Vision 30m/98ft Video & Audio WMax. Resolution 2880*1620 Frame Rate Max; 30fps; Self-Adaptive during network transmission Video Compression H. 265 f. H. 264 H. 265 Type Main Profile Video Bit Rate Ultra-HD; HI-Def; Standard. Adaptive bit rate. Audio Bit Rate Self-Adaptive Network Will Standard IEEE802.11b, 802.11g, 802.11n Frequency Range 2.4 GHz ~ 2.4835 GHz Channel Bandwidth Support 20MHz Security WPA-PSK/WPA2-PSK Transmission Rate 11b: 11Mbps,11g: 54Mbps,11n: 72Mbps Wi-Fi Pairing AP pairing AP pairing AP pairing Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Auto Tracking Supports Supports Supports Supports Supports <th< th=""><th>PT Angle</th><th>Pan: 350°, Tilt: 80°</th></th<>	PT Angle	Pan: 350°, Tilt: 80°	
Dug & Night IR-cut filter with auto switch DNR 3D DNR WDR Digital WDR Black & White Night Vision 30m/9sft Video & Audio Max. Resolution 2880*1620 Frame Rate Max: 30fps; Self-Adaptive during network transmission Video Compression H_265 / H_264 H_265 Type Main Profile Video Bit Rate Ultra-HD; Hi-Def; Standard, Adaptive bit rate. Audio Bit Rate Ultra-HD; Hi-Def; Standard, Adaptive bit rate. Audio Bit Rate Ultra-HD; Hi-Def; Standard, Adaptive bit rate. Video Bit Rate Ultra-HD; Hi-Def; Standard, Adaptive bit rate. Network WI-FI Standard Wi-Fi Standard IEEE802.11b, 802.11g, 802.11n Frequency Range 2.4 GHz * 2.4835 GHz Channel Bandwidth Support 2.4835 GHz Channel Bandwidth Support 2.4835 GHz Transmission Rate 1b: 11Mbps,11g: 54Mbps,11n: 72Mbps Wi-Fi Paining AP paining Protocol E2VIZ cloud proprietary protocol Interface Protocol E2VIZ cloud proprietary protocol Wi-Fi St	Minimum Illumination	0.5 Lux @(F1.6, AGC ON), 0 Lux with IR (* data is obtained from EZVIZ laboratories)	
DNR 3D DNR WDR Digital WDR Black & White Night Vision 30 m/98lt Video & Audio Max. Resolution 2880*1620 Frame Rate Max: 30fps; Self-Adaptive during network transmission Video Compression H.265 / H.264 H.265 Type Main Proffie Video Bit Rate Ultra-HD; Hl-Def; Standard. Adaptive bit rate. Audio Bit Rate Self-Adaptive Wetwork Wiscoperation Wi-Fi Standard IEEE802.11b, 802.11g. 802.11n Frequency Range 2.4 GHz ~ 2.4835 GHz Channel Bandwidth Support 20MHz Scurity WPA-PSK/WPAZ-PSK Transmission Rate 11b: 11Mbps,11g: 54Mbps,11n: 72Mbps Wi-Fi Pairing AP pairing Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Mired Network R145 x 1 (10M/100M Adaptive Ethernet Port) Function Supports Suctomized Alert Area Supports Customized Alert Area Supports General Function	Lens Mount	M12	
WDR Digital WDR Black & White Night Vision 30m/98ft Video & Audio Max. Resolution 2880°1620 Frame Rate Max: 30fps; Self-Adaptive during network transmission Video Compression H. 265 / H. 264 HL.265 Type Main Profile Video Bit Rate Ultra-HD; Hi-Def; Standard. Adaptive bit rate. Audio Bit Rate Self-Adaptive Network WIF1 Standard Frequency Range 2.4 GHz ~ 2.4835 GHz Channel Bandwidth Support 20MHz Security WPA-PSK/WPA2-PSK Transmission Rate 11b: 11Mbps, 11g: 54Mbps, 11n: 72Mbps Wi-Fi Pairing AP pairing Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Wired Network RI45 x 1 (10M/100M Adaptive Ethernet Port) Function Supports Sust Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage EZVIZ Cloud	-		
Black & White Night Vision 30m/98ft Video & Audio Max. Resolution 2880*1620 Frame Rate Max 30fps, Self-Adaptive during network transmission Video Compression H 2.55 / H .264 H.265 Type Main Profile Video Bit Rate Ultra-HD; Hi-Def; Standard. Adaptive bit rate. Audio Bit Rate Ultra-HD; Hi-Def; Standard. Adaptive bit rate. Audio Bit Rate Ultra-HD; Hi-Def; Standard. Adaptive bit rate. Wetwork Wetwork Wetwork WiF Bandard IEEE802.11b, 802.11g, 802.11n Everuty WPA-PSK MPA2-PSK Total Bandwidth Support 20MHz Wee, Sewity WPA-PSK/WPA2-PSK Transmission Rate 11b; 11/Mbps, 11g; 54Mbps, 11n; 72Mbps WiFe Pairing A Pairing Protocol EZVIZ Cloud proprietary protocol Mirea Protocol <th colsp<="" th=""><th></th><th></th></th>	<th></th> <th></th>		
Video & Audio Max. Resolution 2880°1620 Frame Rate Max: 30fps; Self-Adaptive during network transmission Video Compression H.265 / H.264 H.265 Type Main Profile Video Bit Rate Ultra-HD; Hi-Def; Standard. Adaptive bit rate. Audio Bit Rate Self-Adaptive Network Wi-Fi Standard IEEE802.11b, 802.11g, 802.11n Frequency Range 2.4 GHz ~ 2.4835 GHz Channel Bandwidth Support 20MHz Security WPA-PSK/WPA2-PSK Transmission Rate 11b: 11Mbps,11g; 54Mbps,11n:72Mbps Wi-Fi Pairing AP pairing Protocol EZVIZ cloud proprietary protocol Use of Network R34 1 (10M/100M Adaptive Ethernet Port) Function Supports Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Guestonized Alert Area Supports Two-way Talk Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage EZVIZ Cloud Storag	WDR	Digital WDR	
Max. Resolution 2880*1620 Frame Rate Max: 30fps; Self-Adaptive during network transmission Video Compression H. 265 Type Main Profile Video Bit Rate Ultra-Hb.J.H-Def; Standard. Adaptive bit rate. Audio Bit Rate Self-Adaptive Network VI-FI Standard Frequency Range 2.4 GHz * 2.4835 GHz Channel Bandwidth Support 20MHz Security WPA-PSK/WPA2-PSK Transmission Rate 11b: 11Mbps,11g: 54Mbps,11n:72Mbps Wi-Fi Pairing AP pairing Protocol E2VIZ cloud proprietary protocol Interface Protocol E2VIZ cloud proprietary protocol Wired Network R.145 x 1 (10M/100M Adaptive Ethernet Port) Function Supports Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Customized Alert Area Supports Two-way Talk Supports Clocal Storage Micro SD card slot (Up to 512GB) Cloud Storage E2VIZ Cloud Storage Cloud Storage E2VIZ Cloud Storage	Black & White Night Vision	30m/98ft	
Frame Rate Max: 30fps; Self-Adaptive during network transmission Video Compression H.265 / H.264 H.265 Type Main Profile Video Bit Rate Ultra-HD; Hi-Def; Standard. Adaptive bit rate. Audio Bit Rate Self-Adaptive Network Wi-Fi Standard IEEE802.11b, 802.11g, 802.11n Frequency Range 2.4 GHz ~ 2.4835 GHz Channel Bandwidth Support 20MHz Security WPA-PSK/WPA2-PSK Transmission Rate 11b: 11Mbps,11g:54Mbps,11n:72Mbps Wi-Fi Pairing AP pairing AP pairing Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Wired Network R145 × 1 (10M/100M Adaptive Ethernet Port) Function Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Trackling Supports Two-way Talk Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Cloud Storage Micro SD card slot (Up to 512GB) Cloud Storage EZVIZ Cloud Storage General Operating Conditions Individual Support Power Supply Dc 12V/1A Power Consumption MAX. 12W Dimensions 100× 136× 140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140* 140* 140* 140* 120 mm (5.51 × 5.51× 7.56 inch) Net Weight: 539.7g;	Video & Audio		
Video Compression H.265 Type Main Profile Video Bit Rate Ultra-HD, Hi-Def; Standard. Adaptive bit rate. Audio Bit Rate Self-Adaptive Network Wi-Fi Standard IEEE802.11b, 802.11g, 802.11n Frequency Range 2.4 GHz ~ 2.4835 GHz Channel Bandwidth Support 20MHz Security WPA-PSK/WPA2-PSK Transmission Rate 11b: 11Mbps,11g:54Mbps,11n:72Mbps Wi-Fi Pairing AP pairing Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Wired Network RJ45 × 1 (10M/100M Adaptive Ethernet Port) Function Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Customized Alert Area Supports Two-way Talk Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Local Storage Micro SD card slot (Up to 512GB) Cloud Storage EZVIZ Cloud Storage For the Storage (International Storage (International Storage) General Veatherproof Desig	Max. Resolution	2880*1620	
H.265 Type Main Profile Video Bit Rate Ultra-HD; Hi-Def; Standard. Adaptive bit rate. Audio Bit Rate Self-Adaptive Network Wi-Fi Standard IEEE802.11b, 802.11g, 802.11n Frequency Range 2.4 GHz ~ 2.4835 GHz Channel Bandwidth Support 20MHz Security WPA-PSK/WPA2-PSK Transmission Rate 11b: 11Mbps,11g:54Mbps,11n:72Mbps Wi-Fi Pairing AP pairing Protocol E2VIZ cloud proprietary protocol Interface Protocol E2VIZ cloud proprietary protocol Wired Network RJ45 × 1 (10M/100M Adaptive Ethernet Port) Function Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Micro SD card slot (Up to 512GB) Cloud Storage E2VIZ Cloud Storage General E2VIZ Cloud Storage General Operating Conditions 30°C to 50°C (-22°F to 122°F) humidity 95% or less (non-condensing) IP Grade Weather proof Design Power Consumption MAX. 12W Dimensions 100× 136× 140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 ×5.51 × 5.51 × 7.56 inch)	Frame Rate	Max: 30fps; Self-Adaptive during network transmission	
Video Bit Rate Ultra-HD; Hi-Def; Standard. Adaptive bit rate. Audio Bit Rate Self-Adaptive Network Wi-Fi Standard IEEE802.11b, 802.11g, 802.11n Frequency Range 2.4 GHz ~ 2.4835 GHz Channel Bandwidth Support 20MHz Security WPA-PSK/WPA2-PSK Transmission Rate 11b: 11Mbps,11g: 54Mbps,11n: 72Mbps Wi-Fi Pairing AP pairing Protocol EZVIZ cloud proprietary protocol Uitraface Protocol EZVIZ cloud proprietary protocol Wired Network RJ45 x 1 (10M/100M Adaptive Ethernet Port) Function Supports Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Customized Alert Area Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Micro SD card slot (Up to 512GB) Cloud Storage EZVIZ Cloud Storage General Operating Conditions Packaging Conditions 130°C to 50°C (-22°F to 122°F) humidity 95% or less (non-condensing) IP Grade Weatherproof Design Power Consumption MAX: 12W <tr< th=""><th>Video Compression</th><th>H.265 / H.264</th></tr<>	Video Compression	H.265 / H.264	
Network Wi-Fi Standard IEEE802.11b, 802.11g, 802.11n Frequency Range 2.4 GHz ~ 2.4835 GHz Channel Bandwidth Support 20MHz Security WPA-PSK/WPA2-PSK Transmission Rate 11b: 11Mbps,11g:54Mbps,11n:72Mbps Wi-Fi Pairing AP pairing Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Wired Network RJ45 × 1 (10M/100M Adaptive Ethernet Port) Function Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Two-way Talk Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Local Storage Micro SD card slot (Up to 512GB) Cloud Storage EZVIZ Cloud Storage General Operating Conditions -30°C to 50°C (-22 °F to 122 °F) humidity 95% or less (non-condensing) IP Grade Weatherproof Design Power Consumption MAX. 12W Dimensions 100×136×140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 ×5.51× 7.56 inch) Weight: 539.7g;	H.265 Type	Main Profile	
Network Wi-Fi Standard IEEE802.11b, 802.11g, 802.11n Frequency Range 2.4 GHz ~ 2.483 GHz Channel Bandwidth Support 20MHz Security WPA-PSK/WPA2-PSK Transmission Rate 11b: 11Mbps,11g:54Mbps,11n:72Mbps Wi-Fi Pairing AP pairing Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Wired Network RJ45 × 1 (10M/100M Adaptive Ethernet Port) Function Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Gustomized Alert Area Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Local Storage Micro SD card slot (Up to 512GB) Cloud Storage EzVIZ Cloud Storage General Operating Conditions -30°C to 50°C (-22 °F to 122 °F) humidity 95% or less (non-condensing) IP Grade Weather proof Design Power Consumption MAX. 12W Dimensions 100× 136× 140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 ×5.51× 7.56 inch) Neight 539.7g;	Video Bit Rate	Ultra-HD; Hi-Def; Standard. Adaptive bit rate.	
Wi-Fi Standard IEEE802.11b, 802.11g, 802.11n Frequency Range 2.4 GHz ~ 2.4835 GHz Channel Bandwidth Support 20MHz Security WPA-PSK/WPA2-PSK Transmission Rate 11b: 11Mbps,11g:54Mbps,11n:72Mbps Wi-Fi Pairing AP pairing Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Wired Network RJ45 × 1 (10M/100M Adaptive Ethernet Port) Function Smart Alarn Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Customized Alert Area Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Cloud Storage Gloud Storage Gloud Storage General Cloud Storage General Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 140*140*192mm (5.51 × 5.51 × 7.56 inch) Weight* Weight* Micro Sp. 24 GHZ Max 1 ×	Audio Bit Rate	Self-Adaptive Self-Adaptive	
Frequency Range 2.4 GHz ~ 2.4835 GHz Channel Bandwidth Support 20MHz Security WPA-PSK/WPA2-PSK Transmission Rate 11b: 11Mbps,11g:54Mbps,11n:72Mbps Wi-Fi Pairing AP pairing Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Wired Network RJ45 × 1 (10M/100M Adaptive Ethernet Port) Function Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Customized Alert Area Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Local Storage Micro SD card slot (Up to 512GB) Cloud Storage General Operating Conditions Anti-Midity 95% or less (non-condensing) IP Grade Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100×136×140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 × 5.51× 7.56 inch) Weight: 539.7g;	Network		
Channel Bandwidth Support 20MHz Security WPA-PSK/WPA2-PSK Transmission Rate 11b: 11Mbps,11g:54Mbps,11n:72Mbps Wi-Fi Pairing AP pairing Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Wired Network RJ45 × 1 (10M/100M Adaptive Ethernet Port) Function AI-Powered Human / Vehicle Shape Detection Auto Tracking Supports Customized Alert Area Supports Two-way Talk Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Micro SD card slot (Up to 512GB) Cloud Storage EZVIZ Cloud Storage General EZVIZ Cloud Storage General Up to 512 °F) humidity 95% or less (non-condensing) humidity 95% or less (non-condensing) IP Grade Weather proof Design Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100 x 136 x 140mm (3.94 x 5.35 x 5.51inch) Neight Net Weight: 539.7g;	Wi-Fi Standard	IEEE802.11b, 802.11g, 802.11n	
Security WPA-PSK/WPA2-PSK Transmission Rate 11b: 11Mbps,11g:54Mbps,11n:72Mbps Wi-Fi Pairing AP pairing Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Wired Network RJ45 × 1 (10M/100M Adaptive Ethernet Port) Function Function Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Customized Alert Area Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Local Storage Cloud Storage Micro SD card slot (Up to 512GB) Cloud Storage EZVIZ Cloud Storage General EZVIZ Cloud Storage General Operating Conditions IP Grade Weatherproof Design Power Supply DC 12V/IA Power Consumption MAX. 12W Dimensions 100 x 136 x 140mm (3.94 x 5.35 x 5.51inch) Packaging Dimensions 140 * 140 * 192mm (5.51 x 5.51 x 7.56 inch) Weight: 539.7g;	Frequency Range	2.4 GHz ~ 2.4835 GHz	
Transmission Rate Wi-Fi Pairing AP pairing AP pairing Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Wired Network RJ45 × 1 (10M/100M Adaptive Ethernet Port) Function Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Customized Alert Area Supports Customized Alert Area Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Local Storage Micro SD card slot (Up to 512GB) Cloud Storage General Operating Conditions -30°C to 50°C (-22 °F to 122 °F) humidity 95% or less (non-condensing) IP Grade Weatherproof Design Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100×136×140mm (3.94 × 5.35×5.51inch) Packaging Dimensions Net Weight: 539.7g;	Channel Bandwidth	Support 20MHz	
Wi-Fi Pairing AP pairing Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Wired Network RJ45 × 1 (10M/100M Adaptive Ethernet Port) Function Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Customized Alert Area Supports Customized Alert Area Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Local Storage Micro SD card slot (Up to 512GB) Cloud Storage EZVIZ Cloud Storage General Operating Conditions Password Protection, Watermark Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100×136×140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 ×5.51× 7.56 inch) Weight* Net Weight: 539.7g;	Security	WPA-PSK/WPA2-PSK	
Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol Wired Network RJ45 × 1 (10M/100M Adaptive Ethernet Port) Function Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Customized Alert Area Supports Two-way Talk Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Local Storage Micro SD card slot (Up to 512GB) Cloud Storage EZVIZ Cloud Storage General Operating Conditions -30°C to 50°C (-22 °F to 122 °F) humidity 95% or less (non-condensing) IP Grade Weatherproof Design Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100× 136× 140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 × 5.51× 7.56 inch) Net Weight: 539.7g;	Transmission Rate	11b: 11Mbps,11g :54Mbps,11n :72Mbps	
Interface Protocol Wired Network RJ45 × 1 (10M/100M Adaptive Ethernet Port) Function Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Customized Alert Area Supports Two-way Talk Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Local Storage Micro SD card slot (Up to 512GB) Cloud Storage EZVIZ Cloud Storage General Operating Conditions IP Grade Weatherproof Design Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 140*140*192mm (5.51 ×5.551 × 7.56 inch) Net Weight: 539.7g;	Wi-Fi Pairing	AP pairing	
Wired Network RJ45 × 1 (10M/100M Adaptive Ethernet Port) Function Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Customized Alert Area Supports Two-way Talk General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Local Storage Micro SD card slot (Up to 512GB) Cloud Storage EZVIZ Cloud Storage General Operating Conditions -30°C to 50°C (-22°F to 122°F) humidity 95% or less (non-condensing) IP Grade Weatherproof Design Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100×136×140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 × 5.51× 7.56 inch) Weight: 539.7g;	Protocol	EZVIZ cloud proprietary protocol	
Function Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Customized Alert Area Supports Two-way Talk Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Local Storage Micro SD card slot (Up to 512GB) Cloud Storage EzVIZ Cloud Storage General Operating Conditions Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100×136×140mm (3.94×5.35×5.51inch) Packaging Dimensions 140*140*192mm (5.51×5.51×7.56 inch) Weight Weight Net Weight: 539.7g;	Interface Protocol	EZVIZ cloud proprietary protocol	
Smart Alarm Al-Powered Human / Vehicle Shape Detection Auto Tracking Supports Customized Alert Area Supports Two-way Talk Supports General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Local Storage Micro SD card slot (Up to 512GB) Cloud Storage EZVIZ Cloud Storage General Operating Conditions -30°C to 50°C (-22°F to 122°F) humidity 95% or less (non-condensing) IP Grade Weatherproof Design Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100×136×140mm (3.94×5.35×5.51inch) Packaging Dimensions 140*140*192mm (5.51×5.51×7.56 inch) Weight Net Weight: 539.7g;	Wired Network	RJ45 × 1 (10M/100M Adaptive Ethernet Port)	
Auto TrackingSupportsCustomized Alert AreaSupportsTwo-way TalkSupportsGeneral FunctionAnti-Flicker, Dual-Stream, Heart Beat, Password Protection, WatermarkStorageMicro SD card slot (Up to 512GB)Cloud StorageEZVIZ Cloud StorageGeneralEZVIZ Cloud StorageOperating Conditions-30°C to 50°C (-22 °F to 122 °F) humidity 95% or less (non-condensing)IP GradeWeatherproof DesignPower SupplyDC 12V/1APower ConsumptionMAX. 12WDimensions100× 136× 140mm (3.94 × 5.35× 5.51inch)Packaging Dimensions140*140*192mm (5.51 ×5.51× 7.56 inch)WeightNet Weight: 539.7g;	Function		
Customized Alert AreaSupportsTwo-way TalkSupportsGeneral FunctionAnti-Flicker, Dual-Stream, Heart Beat, Password Protection, WatermarkStorageUccal StorageLocal StorageMicro SD card slot (Up to 512GB)Cloud StorageEZVIZ Cloud StorageGeneral-30°C to 50°C (-22°F to 122°F) humidity 95% or less (non-condensing)IP GradeWeatherproof DesignPower SupplyDC 12V/1APower ConsumptionMAX. 12WDimensions100×136×140mm (3.94 × 5.35×5.51inch)Packaging Dimensions140*140*192mm (5.51 ×5.51×7.56 inch)WeightNet Weight: 539.7g;	Smart Alarm	Al-Powered Human / Vehicle Shape Detection	
Two-way Talk General Function Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark Storage Local Storage Micro SD card slot (Up to 512GB) Cloud Storage EZVIZ Cloud Storage General Operating Conditions IP Grade Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100×136×140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 × 5.51× 7.56 inch) Weight Weight Net Weight: 539.7g;	Auto Tracking	Supports	
General FunctionAnti-Flicker, Dual-Stream, Heart Beat, Password Protection, WatermarkStorageLocal StorageMicro SD card slot (Up to 512GB)Cloud StorageEZVIZ Cloud StorageGeneral-30°C to 50°C (-22°F to 122°F) humidity 95% or less (non-condensing)IP GradeWeatherproof DesignPower SupplyDC 12V/1APower ConsumptionMAX. 12WDimensions100×136×140mm (3.94×5.35×5.51inch)Packaging Dimensions140*140*192mm (5.51×5.51×7.56 inch)WeightNet Weight: 539.7g;	Customized Alert Area	Supports	
Local Storage Micro SD card slot (Up to 512GB) Cloud Storage EZVIZ Cloud Storage General Operating Conditions -30°C to 50°C (-22 °F to 122 °F) humidity 95% or less (non-condensing) IP Grade Weatherproof Design Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100× 136× 140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 ×5.51× 7.56 inch) Weight Net Weight: 539.7g;	Two-way Talk	Supports	
Local StorageMicro SD card slot (Up to 512GB)Cloud StorageEZVIZ Cloud StorageGeneral-30°C to 50°C (-22°F to 122°F) humidity 95% or less (non-condensing)IP GradeWeatherproof DesignPower SupplyDC 12V/1APower ConsumptionMAX. 12WDimensions100×136×140mm (3.94×5.35×5.51inch)Packaging Dimensions140*140*192mm (5.51×5.51×7.56 inch)WeightNet Weight: 539.7g;	General Function	Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark	
Cloud Storage General Operating Conditions IP Grade Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100× 136× 140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions EZVIZ Cloud Storage EZVIZ Cloud Storage F to 122 °F to 122 °F to 122 °F to 122 °F humidity 95% or less (non-condensing) Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100× 136× 140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 ×5.51× 7.56 inch) Weight	Storage		
General Operating Conditions -30°C to 50°C (-22 °F to 122 °F) humidity 95% or less (non-condensing) IP Grade Weatherproof Design Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100×136×140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 ×5.51× 7.56 inch) Weight Net Weight: 539.7g;	Local Storage	Micro SD card slot (Up to 512GB)	
-30°C to 50°C (-22 °F to 122 °F) humidity 95% or less (non-condensing) IP Grade Weatherproof Design Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100× 136× 140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 ×5.51× 7.56 inch) Weight Net Weight: 539.7g;	Cloud Storage	EZVIZ Cloud Storage	
humidity 95% or less (non-condensing) Weatherproof Design Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100× 136× 140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 ×5.51× 7.56 inch) Weight Net Weight: 539.7g;	General		
Power Supply DC 12V/1A Power Consumption MAX. 12W Dimensions 100× 136× 140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 ×5.51× 7.56 inch) Weight Net Weight: 539.7g;		humidity 95% or less (non-condensing)	
Power Consumption MAX. 12W Dimensions 100× 136× 140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 ×5.51× 7.56 inch) Weight Net Weight: 539.7g;	IP Grade	Weatherproof Design	
Dimensions 100× 136× 140mm (3.94 × 5.35× 5.51inch) Packaging Dimensions 140*140*192mm (5.51 ×5.51× 7.56 inch) Weight Net Weight: 539.7g;	Power Supply	DC 12V/1A	
Packaging Dimensions 140*140*192mm (5.51 ×5.51× 7.56 inch) Net Weight (5.51 ×5.51× 7.56 inch)	Power Consumption	MAX. 12W	
Weight Net Weight: 539.7g;	Dimensions	100× 136× 140mm (3.94 × 5.35× 5.51inch)	
Weight	Packaging Dimensions	140*140*192mm (5.51 ×5.51× 7.56 inch)	
	Weight		

